


MULTIS EP NA



GREASE



Multi-Purpose, Lithium Grease

APPLICATIONS

**Multi-purpose,
extreme pressure
industrial & automotive
grease**

- **MULTIS EP NA GREASES** are high quality lithium greases designed for the economical lubrication of all applications operating under severe conditions.
- **MULTIS EP NA GREASES** are multi-purpose greases available in a wide range of grades. They are formulated for the lubrication of ball bearings, plain bearings, and roller bearings subjected to impacts and vibrations in transportation, agriculture, and off-road vehicles. These greases are also suitable for general purpose industrial applications requiring a NLGI 2 grade, extreme pressure grease. Always avoid contamination of the grease by dust and/or dirt when applying. Preferably use a pneumatic pump system or cartridges.

SPECIFICATIONS

- ISO 6743-9: L-XBEHB-2
- DIN 51502: KP2P-20
- NLGI LB (#2 grade)

ADVANTAGES

Multipurpose

Multiple grades

No harmful substances

- Multiple grades meet a wide variety of requirements and applications.
- Miscible with the majority of other conventional soap greases.
- Durable and resistant to water, pollution, and temperature variations.
- Very good adhesion to metals.
- Good mechanical and thermal stability.
- Excellent anti-rust and anti-corrosion properties.
- Does not contain lead or any other heavy metals harmful to humans or the environment.

TYPICAL PROPERTIES--MULTIS EP NA GREASES

	000	00	0	1	2
NLGI Grade	000	00	0	1	2
Visual appearance, smooth amber grease	Yes	Yes	Yes	Yes	Yes
Thickener type, lithium 12-hydroxy stearate	Yes	Yes	Yes	Yes	Yes
Penetration worked 60x ASTM D 217	460	430	385	330	280
Dropping point, °F (°C) ASTM D 2265	320 (160)	360 (182)	360 (182)	360 (182)	360 (182)
4 ball weld load, kg. ASTM D 2596	250	250	250	250	250
Timken OK load, lbs ASTM D 2509	-	45	45	60	60
Base oil viscosity @ 40°C, cSt ASTM D 445	320	160	180	180	180
Estimated operating range, °F	-20 to 290	-20 to 290	-10 to 290	0 to 290	0 to 290

TOTAL Specialties USA, Inc.

Linden, NJ 07036
5 North Stiles Street
1-800-323-3198
www.totalspecialties.com

MULTISEP

6-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at www.totalspecialties.com. Copyright 2016 All rights reserved.